

Claims

1. A support for a shower head (8) having
  - 1.1 a mounting fixture (2) for mounting the support such that the latter may be adjusted, if desired,
  - 1.2 an arm (5, 15) jutting out of the mounting fixture (2),
  - 1.3 a receptacle (16) for a shower head (8) arranged in the vicinity of the far end of the arm (5, 15), and
  - 1.4 at least one additional shower fixture (11) attached to the arm (5, 15).
2. A shower support according to claim 1, wherein the additional shower fixture (11) may be supplied with water independently of the shower head (8).
3. A shower support according to claim 1 or claim 2 having a channel passing through the arm (5, 15) and leading to the additional shower fixture (11).
4. A shower support according to any of the foregoing claims, wherein the arm (5, 15) is configured in the form of a length of hollow, profiled stock, at least out to the additional shower fixture (11).
5. A shower support according to any of the foregoing claims, wherein the additional shower fixture (11) is arranged between the mounting fixture (2) and the far end of the arm (5, 15).
6. A shower support according to any of the foregoing claims, wherein the direction of the jet exiting the additional shower fixture (11) is adjustable.
7. A shower support according to any of the foregoing claims, wherein the additional shower fixture (11) is mounted on the side of the wall-mounting arm (5, 15).

8. A shower support according to any of the foregoing claims, wherein at least one additional shower fixture (11) is mounted on the underside of the wall-mounting arm (5, 15).
9. A shower support according to any of the foregoing claims having several additional shower fixtures (11) and a water-supply conduit common to all additional shower fixtures (11).
10. A shower support according to any of the foregoing claims, wherein the additional shower fixture (11) is nondetachable.
11. A shower support according to any of claims 1 - 9, wherein at least one additional shower fixture (11) is attached to the arm (5, 15) by means of a quick-connect coupler.
12. A shower support according to any of the foregoing claims, wherein the arm (5, 15) is pivotable about a horizontal axis orthogonal to its longitudinal axis on a linkage on the mounting fixture (2).
13. A shower support according to claim 12, wherein the water conduit passes through the linkage.
14. A shower support according to any of the foregoing claims, wherein the arm (5, 15) is configured in the form of a fork.
15. A shower support according to claim 14, wherein the additional shower fixtures (11) are arranged on the outer faces of the tines (14) of the fork.
16. A shower support according to any of the foregoing claims, wherein the shower head (8) is detachable.

17. A shower support according to any of the foregoing claims, wherein the shower head (8) is supplied with water by a hose (10).

-----